

d		
Code	Description	Legend Marking
175	O-I	
175I	OFF-ON	
350	1-0-2 (Reversing)	
375	1-0-2 (90 degrees) (Changeover)	
178	O-I	
178I	OFF-ON	

* For 22.5 mm mounting hole style handle (code HC), select either handle type A, E, I, or L with 48 x 48 mm legend plate size (code 4) only or handle type G or N with 64 x 64 mm legend plate size (code 6) only.

‡ Order 194E- 16 A Type G and N handles as Cat. No. 194E-HE4N-175 or 194E-HE4G-175

§ Use Type G and N with ON-OFF function only (selection "d", code -175)

♣ Cat. No. 194R-HE front-mounting switch only

Frequently Ordered 194L Handles — OFF-ON Base/Front-Mounted 3- and 6-Pole Switch Handles (Switch Body listed on Frequently Ordered* OFF-ON 3-Pole Switch (includes operating shaft) (Handles listed on Bulletin 194E/194L Handles (for use with Bulletin 194E Switches)))

Handle Type	Degree of Protection	Handle Color	Bezel Plate Size	For Use With	Legend Plate Marking	Cat. No.
E	IP66 (UL Type 1) (UL Type 3/3R/12)	Black/Grey	48 x 48 mm (1-57/64 x 1-57/64 in.)	194E-16...63 A	0-1	194L-HE4E-175
				194L-E12...40 A, -1753 194L-A12...40 A, -1753	OFF-ON	194L-HE4E-175I
L		Red/Yellow	48 x 48 mm (1-57/64 x 1-57/64 in.)	194E-16...63 A	0-1	194L-HE4L-175
				194L-E12...40 A, -1753 194L-A12...40 A, -1753	OFF-ON	194L-HE4L-175I
G	IP66 (UL Type 3/3R/12)	Black/Grey	54 x 54 mm (2-1/8 x 2-1/8 in.)	194E-16 A	0-1 OFF-ON	194E-HE4G-175
			67 x 67 mm (2-41/64 x 2-41/64 in.)	194E-25...100 A 194L-E12...40 A, -1753 194L-A12...40 A, -1753	0-1 OFF-ON	194L-HE6G-175
			88 x 88 mm (3-15/32 x 3-15/32 in.)	194E-40...100 A	0-1 OFF-ON	194L-HE8G-175
N		Red/Yellow	54 x 54 mm (2-1/8 x 2-1/8 in.)	194E-16 A	0-1 OFF-ON	194E-HE4N-175
			67 x 67 mm (2-41/64 x 2-41/64 in.)	194E-25...100 A 194L-E12...40 A, -1753 194L-A12...40 A, -1753	0-1 OFF-ON	194L-HE6N-175
			88 x 88 mm (3-15/32 x 3-15/32 in.)	194E-40...100 A	0-1 OFF-ON	194L-HE8N-175
L	IP66 (UL Type 3/3R/12)	Red/Yellow	48 x 48 mm (1-57/64 x 1-57/64 in.)	194L-E12...40 A, -1753	0-1	194L-HC4L-175
					OFF-ON	194L-HC4L-175I

Bulletin 194E Open and Enclosed Switch Kits

Cat. No. Explanation

194E - Y 32 - 1753 - 6N

a b c d

a	
Code	Installation Type
A	Base/DIN mounting, open type switch
E	Front/Door mounting, open type switch
Y	Enclosed base mounting switch with handle (Uses IP66 ABS thermoplastic enclosure)

b	
Code	Load Size
16	16 A*
25	25 A
32	32 A
40	40 A
63	63 A
80	80 A
100	100 A

* For 16 A Enclosed Switch: use "16M" (3-pole enclosure has M16/20 knockouts, 6-pole 16 A enclosure has M25/32 knockouts). For 25/32 A Enclosed Switch with M20/25 metric knockouts: use "25M" or "32M".



c	
Code	Configuration
1753	3-pole OFF/ON (90°)
1756	6-pole OFF/ON (90°)

d	
Code	Handle Style
4N	194E-HE4N-175 (use with 16 A switch)
4G	194E-HE4G-175 (use with 16 A switch)
4A	194L-HE4A-175 (use with 16...100 A switch)
6N	194L-HE6N-175 (use with 25...100 A switch)
6G	194L-HE6G-175 (use with 25...100 A switch)
6A	194L-HE6A-175 (use with 25...100 A switch)

Frequently Ordered Switch Kits — OFF-ON Front- and Base-Mounted 3-Pole Switch With Cat. No. 194L-HE6N-175 Red/Yellow Handle

	Function Switching Angle	Rated Current [A]	AC23A Rated Power [kW] at 690V AC	HP @ 480V AC 60 Hz, 3Phase	Base-Mounted Cat. No.	Front-Mounted Cat. No.
		25	7.5	10	194E-A25-1753-6N	194E-E25-1753-6N
		32	11	15	194E-A32-1753-6N	194E-E32-1753-6N
		63	18.5	25	194E-A63-1753-6N	194E-E63-1753-6N

Base-Mounting Distribution Switches (handles are pre-assembled to switch)

	Function Switching Angle	No. of Circuits	Contact Target		Handle Color	Legend Plate Marking	Lockable (One Padlock)	Rated Current [A]	AC23A Rated Power [kW] at 690V AC	Hp @ 480V AC 60 Hz, 3Phase	Cat. No.
			OFF/0	ON/1							
		1	O	X	Red/Yellow	0-1	Yes	25	11	—	194E-A25-1753-R
			O	X	Black/Grey	0-1	No				194E-A25-1753-O
		2	O	X	Red/Yellow	0-1	Yes	32	15	—	194E-A32-1753-R
			O	X	Black/Grey	0-1	No				194E-A32-1753-O

Frequently Ordered Enclosures — 3- and 6-Pole Enclosed Switches With Cat. No. 194L-HE6N-175 Red/Yellow Operating Handles