

## 700 to 1500 Terminal Selections

The table shows the catalog number breakdown for the 700 to 1500 terminals.

| Bulletin | Input Type       | Display Size  | Display Type | Communication <sup>(1)</sup>   | Power  | Operating System                          | Special Option       |
|----------|------------------|---------------|--------------|--------------------------------|--------|---|----------------------|
| 2711P-   | K = Keypad       | 7 = 6.5 in.   | C = Color    | 4 = Ethernet, RS-232 & (2) USB | A = AC | 8 = Windows CE 6.0                        | K = Conformal-Coated |
|          | T = Touch        | 10 = 10.4 in. |              |                                | D = DC | 9 = Windows CE 6.0 with extended features |                      |
|          | B = Keypad/Touch | 12 = 12.1 in. |              |                                |        |   |                      |
|          |                  | 15 = 15 in.   |              |                                |        |   |                      |

(1) Optional communication modules are available as separate catalog numbers.

**Table 13 - PanelView Plus 6 - 700 to 1500 Terminals without Extended Features**

| Cat. No.          |                |               | Display  |       | Communication |          | Input Power | Memory (MB) <sup>(1)</sup> |                                      |
|-------------------|----------------|---------------|----------|-------|---------------|----------|-------------|----------------------------|--------------------------------------|
| Keypad            | Touch          | Keypad/Touch  | Size     | Type  | RS-232        | Ethernet |             | RAM                        | Nonvolatile                          |
| <b>700 Model</b>  |                |               |          |       |               |          |             |                            |                                      |
| 2711P-K7C4D8      | 2711P-T7C4D8   | 2711P-B7C4D8  | 6.5-in.  | Color | •             | •        | DC          | 512                        | 512 (approx. 79 MB free user memory) |
| -                 | 2711P-T7C4D8K  | -             |          |       | •             | •        | DC          |                            |                                      |
| 2711P-K7C4A8      | 2711P-T7C4A8   | 2711P-B7C4A8  |          |       | •             | •        | AC          |                            |                                      |
| <b>1000 Model</b> |                |               |          |       |               |          |             |                            |                                      |
| 2711P-K10C4D8     | 2711P-T10C4D8  | 2711P-B10C4D8 | 10.4-in. | Color | •             | •        | DC          | 512                        | 512 (approx. 79 MB free user memory) |
| 2711P-K10C4A8     | 2711P-T10C4A8  | 2711P-B10C4A8 |          |       | •             | •        | AC          |                            |                                      |
| <b>1250 Model</b> |                |               |          |       |               |          |             |                            |                                      |
| 2711P-K12C4D8     | 2711P-T12C4D8  | 2711P-B12C4D8 | 12.1-in. | Color | •             | •        | DC          | 512                        | 512 (approx. 79 MB free user memory) |
| -                 | 2711P-T12C4D8K | -             |          |       | •             | •        | DC          |                            |                                      |
| 2711P-K12C4A8     | 2711P-T12C4A8  | 2711P-B12C4A8 |          |       | •             | •        | AC          |                            |                                      |
| <b>1500 Model</b> |                |               |          |       |               |          |             |                            |                                      |
| 2711P-K15C4D8     | 2711P-T15C4D8  | 2711P-B15C4D8 | 15-in.   | Color | •             | •        | DC          | 512                        | 512 (approx. 79 MB free user memory) |
| 2711P-K15C4A8     | 2711P-T15C4A8  | 2711P-B15C4A8 |          |       | •             | •        | AC          |                            |                                      |

(1) The logic module supports FactoryTalk View Machine Edition software, version 6.0 or later, FactoryTalk ViewPoint software version 1.2 or later, and the Windows CE 6.0 operating system.