

Rittal – The System.

Faster – better – everywhere.

Thermostat Enclosure internal thermostat – SK 3110.000

Date : Mar 21, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Thermostat Enclosure internal thermostat – SK 3110.000

created: 21.03.2018 on www.rittal.com/com-en



Product description

Description: Particularly suitable for controlling fans, heaters and heat exchangers, this thermostat can also be used as a signal generator for monitoring the enclosure internal temperature.

Benefits: Time-saving connection technique using a terminal strip with a screw connection from the outside
Flexible mounting on a vertical or horizontal 35 mm support rail to EN 50 022, and snap fastening in the enclosure section or on the mounting plate using the supplied adaptor

Technical specifications: Bi-metal controller as a temperature-sensitive element with thermal feedback
Contact population: Single-pole change-over contact as a quick-break contact
Permissible contact load: Category 5 – 3 (heating) AC 10 (4) A (inductive load at $\cos \varphi = 0.6$)/category 5- 4 (cooling): AC 5 (4) A (inductive load at $\cos \varphi = 0.6$)/DC = max. 30 W
Switching difference: approx. $1 \text{ K} \pm 0.8 \text{ K}$

Colour: RAL 7035

Product features

Rated operating voltage: 24 V - 230 V, 1~
24 V - 60 V (DC)

Dimensions: Width: 71 mm
Height: 71 mm
Depth: 33.5 mm

Temperature range: Setting range: +5°C...+60°C

Packs of: 1 pc(s).

Weight/pack:	0.1 kg
EAN:	4028177036598
Customs tariff number:	90321020
ETIM 6.0:	EC002014
ETIM 5.0:	EC002014
eCl@ss 8.0/8.1:	27210707
eCl@ss 7.0/7.1:	27210707
eCl@ss 6.0/6.1:	27210707
eCl@ss 5.1/5.1.4:	27180792
Product description (long):	SK Thermostat, enclosure internal thermostat, 24-230 V, 1~, 24-60 V (DC), Colour RAL 7035, WHD: 71 x 71 x 33.5 mm
Approvals	
Approvals:	UL + C-UL VDE
Certificates:	EAC
Declarations:	Declaration of conformity