

Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling units "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3361.510**

Date : Mar 21, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm wall-mounted cooling units "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3361.510

created: 21.03.2018 on www.rittal.com/com-en



Product description

Material: Sheet steel

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** External circuit IP 34
Internal circuit IP 54

Supply includes: Nano-coated condenser
Fully wired ready for connection (plug-in terminal strip)
Drilling template
Assembly parts

Note: The technical specifications for the wall-mounted cooling unit 3361.540 apply with an external transformer connected.

Product features

**Total cooling output
to DIN EN 14511:** L 35 L 35 at 60 Hz: 0.89 kW
L 35 L 50 at 60 Hz: 0.67 kW

**Air throughput
(unimpeded air flow):** External circuit: 625 m³/h
Internal circuit: 230 m³/h

**Rated operating
voltage:** 115 V, 1~, 60 Hz

Dimensions: Width: 280 mm
Height: 550 mm
Depth: 280 mm

Temperature control:	e-Comfort controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Operating temperature (max.) 60 Hz: +52°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 260 g Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO _{2e}): 0.37 t
Power consumption P_{sub-el}---	L 35 L 35 at 60 Hz: 0.55 kW L 35 L 50 at 60 Hz: 0.66 kW
Rated current (max.):	At 60 Hz: 5.3 A
Start-up current max.:	At 60 Hz: 12 A
Miniature circuit-breaker/fuse:	10 A
Permissible operating pressure (p. max.):	28 bar
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.59
Packs of:	1 pc(s).
Weight/pack:	22 kg
EAN:	4028177429543
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Product description (long):	SK cooling unit Blue e, wall-mounted, 0.89 kW, 115 V, 1~, 60 Hz, Sheet steel, WHD: 280 x 550 x 280 mm

Approvals

Approvals:	CSA TÜV-Geprüfte Leistung TÜV-Geprüfte Sicherheit UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation